



Kuriyama Fire Products Formerly ATI Fire Products

9 VOSE FARM ROAD

PETERBOROUGH, NH 03458

Phone: [888.229.9655](tel:888.229.9655)

Email: info@atifireproducts.com

Part Number AL150B025-NH150, Armtex® Attack Lite™ 25 ft Available Lengths, 1 1/2 in. Size, and NST Coupling Type Blue Lightweight Lined Fire Hose



[General Applications](#) | [Construction](#) | [Service Temperature Range](#) | [Features and Advantages](#) | [Packaging](#) | [Nominal Specifications](#) | [Specifications](#)

General Applications

General Applications

- Municipal fire departments
- Industrial fire brigades
- High rise packs

Construction

Construction

Double-jacket polyester hose with a polyurethane lining. Jacket color options include blue, green, black, orange, purple, red, tan, white and yellow.

Service Temperature Range

Service Temperature

Remains flexible at temperatures as low as -40 °F (-40 °C).

Features and Advantages**Features and Advantages**

- High Burst Rating - 1,200 psi up to 3" diameter.
- Superior Performance - Very low friction loss.
- ARMTEX® ATTACK LITE™ is available in the sizes of 1 1/2", 1 3/4", 2", 2 1/2" and 3".
- Packs Tight - KFP's best packing and easiest to fold double-jacket hose.
- Maintenance Free - Immune to mildew and rot.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- 10-year warranty.

Packaging**Packaging**

Available in 25', 50', and 100' lengths.

Nominal Specifications

Size	1 1/2 in
Color	Blue
Coupling Size	1 1/2 in
Coupling Type	NST
Bowl Size	1 15/16 in
Service Test	400 psi
Proof Test	800 psi
Burst Test	1200 psi

Available Lengths	25 ft
Weight Uncoupled	0.28 lbs/ft

Specifications

Brand	Armtex®
Type	Fire Hose
Material	All-Polyester Double Jacket Polyurethane
Warranty	10 y
Industry Standards	Meets or exceeds National Fire Protection Association (NFPA) 1961